


Emulsifiers for Metalworking Fluids



EMULSIFIERS FROM RENEWABLE RESOURCES

CARING ABOUT NATURE

In water miscible metalworking fluid formulations, emulsifiers constitute one of the most essential components.

As an integral part of metalworking fluid concentrates, emulsifiers enable stable self-emulsification of the concentrate when diluted in water.

Our emulsifiers meet the following requirements:

- Good solubility in base oils
- Good lubricating properties
- Good dermatological and toxicological properties
- Low foaming tendency
- Good heat stability

Our product range includes emulsifiers and co-emulsifiers that are based on renewable resources (e.g. ethoxylated or non-ethoxylated glycerol fatty acid esters, and sorbitan esters*), various fatty acid polyglycol esters and lauryl polyglycol ethers. However, the focus of Evonik is on environmentally friendly glycerol fatty acid esters. In order to emulsify a specific base oil, emulsifiers with suitable HLB values are needed. The required HLB value needs to be adjusted according to the varying fatty acid distribution in vegetable oils or carbon distribution in mineral oils. To match the requirements of a specific oil quality, emulsifiers exhibiting different hydrophilicities and hydrophobicities can be blended (base with co-emulsifier).

* not available in North America



FORMULATION OF EMULSIONS – ASSESSMENT OF EMULSION STABILITY

The careful selection of the components for an emulsion and the evaluation of the latter's stability are important tasks. In many cases the instability of an emulsion becomes obvious in the form of creaming, the appearance of an oil phase at the surface of the system or by the sedimentation of components having a higher density. Thus it is logical to use centrifugation methods in order to speed up the potential destabilization process and to gain a deeper understanding of the factors that determine emulsion stability.

Emulsion stability analyzer LUMiFuge

In our labs we use the stability analyzer LUMiFuge to detect a large variety of demixing phenomena of disperse systems. It is a suitable tool for both screening purposes and optimization of emulsion formulations.

STABILITY OF EMULSIONS USING TAGAT® V 20

TAGAT® V 20 exhibits exceptional emulsifying properties when used in ester oil-based metalworking fluids. Particle size analysis by LUMiFuge technique demonstrates that TAGAT® V 20 yields emulsions of much lower particle size compared to competitive vegetable-based emulsifiers.

Lab bench top analysis verifies that the information determined by the LUMiFuge testing instrument is accurate. After storage over one month at room temperature, the TAGAT® V 20 based emulsion demonstrated superior emulsion stability compared to emulsions based on competitive emulsifiers.




Emulsion stability analyser LUMiFuge

TAGAT® V 20 IMPROVES THE LUBRICATING PROPERTIES OF METALWORKING FLUIDS


TAGAT® V 20 lubricating properties were evaluated with a Megatap II-G 8 (tapping torque test equipment). Torque values are measured as a tap cuts threads into a predrilled hole in a metal specimen. Test results may be illustrated either as a simple torque force value or as relative efficiency (ratio of the average torque value of a reference fluid to that of the test fluid).

The tapping torque test is a relatively good simulation of practical conditions in metalworking operations and is widely used by the metalworking fluid industry to evaluate cutting fluid performance and EP/AW* additive response performance, and should be as large as possible.

* EP = Extreme Pressure, AW = Anti-Wear



Megatap II-G 8 tapping torque equipment



PRODUCT RANGE

EMULSIFIERS

OUR EMULSIFIERS, PARTICULARLY OUR GLYCEROL BASED EMULSIFIERS, EXHIBIT GOOD DERMATOLOGICAL PROPERTIES AND THEY DO NOT HAVE RESTRICTIVE LABELLING.

BASE EMULSIFIERS

TAGAT[®] V 20

Exceptional emulsifying properties combined with excellent lubrication properties for the formulation of metalworking fluids based on vegetable and synthetic ester oils; in combination with alcohol ethoxylates suitable for mineral oil based fluids. Additionally, it reduces the amount of antifoam and corrosion inhibitor required in formulations.

Glycerol-based; **HLB = 8.4**

TAGAT[®] PO 30

Non-ethoxylated emulsifier based on Polyglyceryl-3 oleate, applicable as primary emulsifier in intermediate HLB systems as well as co-emulsifier in combination with more hydrophilic emulsifiers to adjust required HLB of the total formulation. **HLB - 5 (+/- 1)**

TAGAT[®] TO V

Excellent emulsifier for the formulation of metalworking fluids based on naphthenic oils, synthetic oils (e.g. isoocetylolate) and ester oil/mineral oil blends; additionally, it improves lubrication properties of metalworking fluid emulsions.

Glycerol-based; **HLB = 11.3**

TEGO[®] STO 85 V

Excellent emulsifier for paraffin oils, especially in combination with TEGO[®] STO V (soluble in mineral oil).

Sorbitan-based; **HLB = 11.3**

CO-EMULSIFIERS

TEGIN[®] O V

Excellent co-emulsifier in combination with TAGAT[®] V 20 and TAGAT[®] TO V. Glycerol-based; **HLB = 3.3**

TEGO[®] SMO V

Excellent co-emulsifier, especially in combination with TAGAT[®] V 20. Sorbitan-based; **HLB = 4.3**

TEGO[®] STO V

Excellent co-emulsifier, especially in combination with TEGO[®] STO 85 V. Sorbitan-based; **HLB = 1.8**



Europe | Middle East | Africa

Evonik Operations GmbH
Goldschmidtstraße 100
45127 Essen
Germany
Phone +49 201 173-2665
Fax +49 201 173-1990
www.evonik.com

Asia | Pacific

Evonik Specialty Chemicals Co., Ltd.
55, Chungdong Road
Xinzhuang Industry Park
Shanghai, 201108
PR China
Phone +86 21 6119-1125
Fax +86 21 6119-1406

The Americas

Evonik Corporation
P.O. Box 34628
Richmond, VA 23234
USA
Phone +1 804 727-0700
Fax +1 804 727-0855

This information and any recommendations, technical or otherwise, are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purposes. In no event shall Evonik assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. EVONIK EXPRESSLY DISCLAIMS ANY REPRESENTATIONS AND WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, NON-INFRINGEMENT, MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE (EVEN IF EVONIK IS AWARE OF SUCH PURPOSE) WITH RESPECT TO ANY INFORMATION AND RECOMMENDATIONS PROVIDED. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Evonik reserves the right to make any changes to the information and/or recommendations at any time, without prior or subsequent notice.



www.evonik.com/metalworking-fluids