

TEGIN® 90 Pellets

TEGIN® 90 Pellets is an antistatic for polyolefin. It is based on a glycerol fatty acid ester.

Physical properties

Delivery form	pellets
Total monoester content (E.A. 74.01)	> 90 %
Melting point (DGF C-IV 3a)	65 – 70° C
Acid value	max. 3 mg KOH/g
Saponification value	155 – 170 mg KOH/g
Iodine value	max. 2 g J/100g
Free glycerol	< 1.5 %

Application

TEGIN® 90 Pellets is used as an antistatic agent for polyolefin.

Benefits

TEGIN® 90 Pellets reduces the surface resistance and thus the electrostatic charge of polyolefin articles. This results in:

- less dust figures on plastic surfaces, especially on plastic packaging
- less attraction of bacteria to the polyolefin surfaces
- improved melt behaviour in the plastification process; increase of MFI

Dosage

Because of its pellet form TEGIN® 90 Pellets can be dosed dust-free in all common plastics processing steps.

TEGIN® 90 Pellets can be applied in combination with ethoxylated fatty amines.

LDPE

Film	0.1 – 0.2 %
Injection moulding	0.1 – 0.2 %

HDPE

Injection moulding	0.2 – 0.4 %
--------------------	-------------

PP

Film	0.2 – 0.4 %
Injection moulding	0.3 – 0.6 %

Food contact status

BfR Recommendations

The ingredient of TEGIN 90 Pellets is listed in the following BfR Recommendations:

II / III / V / VI / VII / X / XI / XXXIII

EU Regulation 10/2011 and amendments

The ingredient of TEGIN 90 Pellets is listed in the European Regulation 10/2011 without a specific migration limit (SML).

FDA-Regulations

TEGIN® 90 complies to FDA Regulation 21 CFR 184.1505 provided that is used for indirect food contact.

Registration

The components of TEGIN® 90 Pellets are listed in following chemicals inventories:

EINECS, TSCA, ENCS, DSL, ECL, AICS, PICCS, IECSC and ERMA

Storage Stability

TEGIN® 90 Pellets is stable for a minimum of 6 months.

Packaging

25 kg paper bag (600 kg each pallet)

Hazardous goods classification

Information concerning

- classification and labelling according to regulations for transport and for dangerous substances
- protective measures for storage and handling
- measures in case of accidents and fire
- toxicity and ecological effects

is given in our material safety data sheets.

07/2015

Trademark notice and legal notice

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

(Status: July 2015)

Evonik Nutrition & Care GmbH

Goldschmidtstr. 100, 45127 Essen, Germany

Phone Europe +49 201 173-2665, Asia +86 21 61191 125, Americas +1 804 727 0700

interface-performance@evonik.com, www.evonik.com/interface-performance